



Project Name
Model Number
Fixture Type
Notes

PRODUCT IDENTIFICATION

Product Model: LHB Series Highbay/Lowbay
 Product Description: 4’ steel suspended fixture, w/90° mirror reflector, LED strips and drivers
 Product Applications: General Area and task lighting in warehousing, industrial, large retail, w/mounting heights of 12-45’

PRODUCT SPECIFICATIONS

Voltage: 100-277v, 50- 60 Hz
 Power Factor: .96/.998, 120v/277v
 Power Supplied: Quick-connect, remote driver
 THD: 3.11% @ 120v, 8.46% @ 277v

Luminous Efficiency: 142 lm/w LED, 118-122 lm/w Luminaire
 CCT: 5000K
 CRI (Ra): >82

Model Number	Nominal Power	LED Modules	Net Lumens	Replaces	Dimensions	Mounting
LHB80-55	80W	4 x 20w	10,100	320-400w MH	48”x11”x4”	Cable/Pendant/Surface
LHB120-55	120W	2x20w + 2x40w	15,050	400-600w MH	48”x11”x4”	Cable/Pendant/Surface
LHB160-55	160W	4x40w	20,100	500-750w MH	48”x11”x4”	Cable/Pendant/Surface
LHB240-55	240W	6x40w	30,200	800-1200w MH	48”x16”x4”	Cable/Pendant/Surface

The LHB series luminaire represents an incredibly efficient and cost effective solution for areas that have high lumen demand, and medium to high mounting heights. Multiple LED driver design allows convenient partial-power operation for daylight harvesting, occupancy sensing, etc., achieving even higher efficiency. 90° mirror reflector maintains accurate distribution of light. Installation options include surface mount, pendant mount or aircraft cable hanging kits. Quick disconnect whips are available in a variety of lengths, wire gauges, and plug styles.